

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 2003/088268 A3

(51) International Patent Classification⁷: **G21F 9/00**,
C09K 3/00

(21) International Application Number:
PCT/GB2003/001484

(22) International Filing Date: 7 April 2003 (07.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0207876.4 5 April 2002 (05.04.2002) GB

(71) Applicant (for all designated States except US): **BRITISH NUCLEAR FUELS PLC** [GB/GB]; Risley, Warrington, Cheshire WA3 6AS (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DENNIS, Iain**, Stewart [GB/GB]; Springfield Hall, Springfield Road, Leighton Buzzard LU7 2US (GB). **MAYHEW, Phillip**, Antony [GB/GB]; British Nuclear Fuels Plc, Sellafield, Seascale, Cumbria CA20 1PG (GB).

(74) Agent: **HARRISON GODDARD FOOTE**; Belgrave Hall, Belgrave Street, Leeds LS2 8DD (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:

4 March 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **REMOVAL OF BLOCKAGES FROM PIPEWORK**

(57) Abstract: The invention provides a method for the removal of contaminating materials from pipework, the contaminating materials comprising deposits on the pipework which cause a reduction in the effective internal diameter of the pipes and thereby effect a reduction in the rate of flow of a fluid through the pipework, the method comprising treating the contaminating materials with at least one carbamate salt. The methods is also suitable for the treatment of contaminating materials which have a particularly deleterious effect on fluid flow and comprise partial or total blockages of the pipework. The carbamate is preferably in the form of an aqueous solution, and a preferred carbamate salt is ammonium carbamate. The treatment may be carried out in the presence of an additive such as caesium carbonate or ammonium bicarbonate. Optionally the treatment may be accompanied by a pre-treatment or post-treatment with aid, this being followed by a water wash. The method finds particular application in the nuclear processing industry.



WO 2003/088268 A3

INTERNATIONAL SEARCH REPORT

Internat Application No

PCT/03/01484

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G21F9/00 C09K3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G21F C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 34 29 584 A (KISKUN MGTSZ) 11 April 1985 (1985-04-11) the whole document ----	1,2,4, 11-13
A	DATABASE WPI Section Ch, Week 199016 Derwent Publications Ltd., London, GB; Class D15, AN 1990-119060 XP002264899 & JP 02 068192 A (ORIENTAL GIKEN KOGYO), 7 March 1990 (1990-03-07) abstract ----	1,11
A	US 4 946 473 A (JOHNSON THOMAS H) 7 August 1990 (1990-08-07) abstract; claim 1 ----- -/-	1,11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* & * document member of the same patent family

Date of the actual completion of the international search

12 December 2003

Date of mailing of the international search report

29/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Deroubaix, P

INTERNATIONAL SEARCH REPORT

Internal Application No
PC 03/01484

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>DATABASE WPI Section Ch, Week 199912 Derwent Publications Ltd., London, GB; Class A41, AN 1999-136726 XP002264900 & JP 11 005773 A (MITSUBISHI GAS CHEM CO INC), 12 January 1999 (1999-01-12) abstract</p>	1
A	<p>GB 753 386 A (CHEMICAL CONSTRUCTION CORP) 25 July 1956 (1956-07-25) page 2, line 16 - line 51; example 1</p>	1-17

INTERNATIONAL SEARCH REPORT

Internati Application No
PCT 03/01484

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 3429584	A	11-04-1985	HU 188491 B	28-04-1986
			AT 387030 B	25-11-1988
			AT 269884 A	15-04-1988
			BG 48696 A3	15-04-1991
			CH 661934 A5	31-08-1987
			DD 224613 A5	10-07-1985
			DE 3429584 A1	11-04-1985
			PL 249738 A1	04-06-1985
			RO 90387 A1	30-10-1986
JP 2068192	A	07-03-1990	JP 4074073 B	25-11-1992
US 4946473	A	07-08-1990	US 4946982 A	07-08-1990
JP 11005773	A	12-01-1999	NONE	
GB 753386	A	25-07-1956	FR 1099295 A	01-09-1955

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/088268 A2

- (51) International Patent Classification⁷: **G21F 9/00**
- (21) International Application Number: **PCT/GB03/01484**
- (22) International Filing Date: **7 April 2003 (07.04.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
0207876.4 **5 April 2002 (05.04.2002)** **GB**
- (71) Applicant (for all designated States except US): **BRITISH NUCLEAR FUELS PLC** [GB/GB]; Risley, Warrington, Cheshire WA3 6AS (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DENNIS, Iain, Stewart** [GB/GB]; Springfield Hall, Springfield Road, Leighton Buzzard LU7 2US (GB). **MAYHEW, Phillip, Antony** [GB/GB]; British Nuclear Fuels Plc, Sellafield, Seascale, Cumbria CA20 1PG (GB).
- (74) Agent: **HARRISON GODDARD FOOTE**; Belgrave Hall, Belgrave Street, Leeds LS2 8DD (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:**
— *of inventorship (Rule 4.17(iv)) for US only*
- Published:**
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **REMOVAL OF BLOCKAGES FROM PIPEWORK**

(57) Abstract: The invention provides a method for the removal of contaminating materials from pipework, the contaminating materials comprising deposits on the pipework which cause a reduction in the effective internal diameter of the pipes and thereby effect a reduction in the rate of flow of a fluid through the pipework, the method comprising treating the contaminating materials with at least one carbamate salt. The methods is also suitable for the treatment of contaminating materials which have a particularly deleterious effect on fluid flow and comprise partial or total blockages of the pipework. The carbamate is preferably in the form of an aqueous solution, and a preferred carbamate salt is ammonium carbamate. The treatment may be carried out in the presence of an additive such as caesium carbonate or ammonium bicarbonate. Optionally the treatment may be accompanied by a pre-treatment or post-treatment with aid, this being followed by a water wash. The method finds particular application in the nuclear processing industry.

REMOVAL OF BLOCKAGES FROM PIPEWORK

The present invention is concerned with a procedure for the removal of blockages which can occur in pipework during manufacturing operations and industrial processing. More specifically, the invention concerns a method for the removal of build-ups of solids which form in pipework, thereby causing significant operational difficulties.

Manufacturing and other industrial processes are often beset by problems which occur due to the formation of solid deposits within the pipework. Ultimately, such deposits may become sufficiently substantial to lead to blockage of the flow of processing material through the pipework and, in such extreme circumstances, of course, processing or manufacturing operations generally have to be curtailed to allow for removal of the offending blockage.

Consequently, it is accepted procedure to monitor the level of solids build-up in such cases in order that remedial action may be taken in order to remove the deposits before a blockage can occur, thereby preventing the loss of production which would otherwise occur, and the associated financial losses which would accrue. However, although detection of such build-ups of solid is clearly an important part of the preventative procedure, the ability to quickly, cheaply and efficiently remove the offending deposit is also a vital requirement if the viability of the industrial process is to be maintained. It is this aspect of the process which is the concern of the present invention.

The formation of solid deposits within pipework during industrial processing may occur as a consequence of various factors. For instance, a reaction may occur between materials in a solution being carried through the pipework, with the result that a product having poor or limited solubility in the solution is produced and this material then begins to precipitate from solution. Alternatively, some component in a solution may react with the pipework itself in order to give rise to material which is

insoluble in the solution and is thereby deposited from solution. Perhaps most commonly with solutions, however, deposits of material occur simply because the material has somewhat limited solubility in the solution at the outset, and it deposits to an extent from solution as a result of this limited solubility; the formation of a deposit is thereby simply a result of crystallisation from solution, rather than being dependent on the outcome of some – possibly unforeseen – chemical reaction. Similarly, when pipework is being used for the transfer of suspensions, rather than solutions, deposition of material can occur when particles fall out of the suspension.

Clearly, the nature of the deposits which are encountered industrially varies widely, and the number of remedial techniques available for their removal is vast, although most are generally based on either mechanical methods, which physically loosen the deposits from the interior of the pipework by scraping, rubbing, or the like, or chemical techniques, which rely on supplying a liquid which is an efficient solvent for the material forming the deposit, in order to clean it away from the surface of the pipework. Methods which combine these two general approaches are often found to be particularly successful.

Although the range of available techniques known from the prior art is wide and varied and, in most situations commonly encountered in industry, well known methods may be employed to resolve problems which arise, there are still specific materials which, when they occur as deposits in pipework, cause particular difficulties in their removal due to their insolubility in a range of common solvents and their general intractability. It is to the materials which fall within this group that the present invention is directed.

The present inventors have commonly encountered deposits comprising inorganic salts having particularly low solubility levels in most solvents. Examples of such salts include, for example, phosphate, alkylphosphate, molybdate and phosphomolybdate salts; specific examples include the phosphate, butylphosphate, molybdate and phosphomolybdate salts of such as zirconium, tellurium, gadolinium,

caesium, iron and uranium. Materials such as these are commonly found as components of waste and process streams in the nuclear industry.

Consequently, the present invention seeks to provide an efficient method for the
5 removal of such materials, and thereby prevent the severe problems which can
otherwise be caused as a consequence of the stubborn nature of the deposits that are
formed in pipework, and the subsequent blockages that can be encountered. The
method is especially directed towards the removal of deposits which are sufficiently
substantial to cause a reduction in the effective internal diameter of a pipe, and
10 thereby have the capability to cause a reduction in the rate of flow of a fluid through
the pipework. Additionally, of course, the method is required to be capable of
dealing with the more extreme situations wherein severe levels of depositions have
occurred, such that a partial or complete blockage of the pipework has already
occurred. Clearly, such eventualities can cause severe difficulties, and even lead to
15 catastrophic failures, in industrial processes.

In view of the fact that the method of the present invention finds particular
application when dealing with pipeline deposits encountered in the nuclear industry,
the potentially toxic nature of the wash liquors which result from the cleaning
20 operation are of obvious concern and it is important that safe, clean and efficient
methods of disposal should be available for these waste products. Consequently, the
invention also seeks to provide a method of removing these materials from pipework
which does not lead to the generation of toxic or harmful waste streams or by-
products.

25

Thus, according to the present invention, there is provided a method for the removal
of contaminating materials from pipework, said contaminating materials comprising
deposits on the pipework which cause a reduction in the effective internal diameter of
the pipes, and thereby effect a reduction in the rate of flow of a fluid through the
30 pipework, the method comprising treating said contaminating materials with at least
one carbamate salt.

In more extreme situations, said contaminating materials may have a particularly deleterious effect on fluid flow, and comprise partial or total blockages of the pipework.

- 5 Preferably, said carbamate salt comprises an aqueous solution of a carbamate salt. Most preferably, said carbamate salt comprises ammonium carbamate.

The method of the present invention may suitably be performed at room temperature, but the most effective results are achieved when the treatment is carried out at
10 elevated temperatures, preferably above 40°C, most preferably in the region of 60°C. In the case of materials which are particularly difficult to remove, it is desirable that the treatment should be continued for an extended period of time, possibly for several hours. The removal of zirconium molybdate, for example, is preferably carried out by treatment with ammonium carbamate at 60°C for at least two hours.

15

Typical concentrations of carbamate in solution are in the range of from 0.3M to 6.0M, with optimum results being achieved with solutions having a concentration of between 1.0M and 3.0M.

- 20 The efficiency of carbamate salts in achieving the removal of deposits from pipework and the unblocking of pipes is thought in part to be due to the liberation of carbon dioxide which occurs as a result of chemical reaction between acid which has become trapped in the deposited material and the carbamate. The generation of carbon dioxide in this way will assist in mechanically breaking up the deposit or
25 blockage.

Particularly favourable results with certain solid deposits have been achieved when the method of the present invention is carried out in the presence of at least one suitable additive. Examples of additives which have shown advantageous properties
30 include carbonate and bicarbonate salts, with caesium carbonate and ammonium bicarbonate proving to be especially useful in this context. Most preferable is a

mixture of ammonium carbamate and caesium carbonate. Such additives are generally present at a concentration in solution which is in the range from about 0.1M to about 1.0M, with the preferred concentration being around 0.2M. A particularly useful combination has been found to be 0.6M ammonium carbamate with 0.2M caesium carbonate.

In the case of certain particularly stubborn and insoluble materials, it is found that pre-treatment of the deposit or blockage with acid, followed by washing with water, prior to treatment with carbamate may, on occasions, prove beneficial. A preferred acid for this process is nitric acid. The acid is typically provided as a solution having a concentration of between 1M and 5M; generally, a roughly 2M solution is found to be most satisfactory. The pre-treatment with acid and subsequent water wash are most conveniently carried out at room temperature. However, elevated temperatures of up to around 60°C may be employed, if necessary. Alternatively, the acid treatment may be carried out after the treatment with carbamate; in such cases, it is believed that the removal of materials which show limited solubility during the carbamate treatment is facilitated by the physical effects of bubble generation and effervescence resulting from the treatment of the deposit with acid.

Following treatment of the deposit or blockage according to the method of the present invention, there remains a carbamate wash liquor which, particularly in the case of the nuclear industry, requires subsequent disposal or treatment. Fortunately, it has been found that in such cases, after acidification, the wash effluents appear compatible with subsequent evaporation of the liquor, although the volume reduction may be limited due to the possible precipitation of ammonium nitrate. However, care is required during the neutralisation procedure in order to avoid uncontrolled foaming of the mixture.

Specific examples of the successful application of the present invention in the field of nuclear technology include the treatment of pipework used in the processing of Highly Active Liquor according to the following procedures:

Method 1

Treatment with aqueous solution comprising 0.3-1.0M ammonium carbamate and 0.2M caesium carbonate at 60°C for 2 hours.

5

Method 2

- (a) Treatment with 2.0M nitric acid at room temperature; followed by
- (b) Washing with water at room temperature; followed by
- 10 (c) Treatment with 1.0M or 3.0M aqueous ammonium carbamate solution at 60°C for 2 hours.

Method 3

- 15 (a) Treatment with 1.0M or 3.0M aqueous ammonium carbamate solution at 60°C for 2 hours; followed by
- (b) Treatment with 2.0M nitric acid at room temperature; followed by
- (c) Washing with water at room temperature.

20

CLAIMS

1. A method for the removal of contaminating materials from pipework, said contaminating materials comprising deposits on the pipework which cause a
5 reduction in the effective internal diameter of the pipes and thereby effect a reduction in the rate of flow of a fluid through the pipework, the method comprising treating said contaminating materials with at least one carbamate salt.
- 10 2. A method as claimed in claim 1 wherein said contaminating materials comprise partial or total blockages of the pipework.
3. A method as claimed in claim 1 or 2 wherein said carbamate salt comprises an aqueous solution of a carbamate salt.
- 15 4. A method as claimed in claim 1, 2 or 3 wherein said carbamate salt comprises ammonium carbamate.
5. A method as claimed in any one of claims 1 to 4 wherein said treatment is
20 carried out at a temperature in the range of from 40°C to 60°C.
6. A method as claimed in claim 5 wherein said temperature is in the region of 60°C.
- 25 7. A method as claimed in any preceding claim wherein said treatment is continued for an extended period of time.
8. A method as claimed in claim 7 wherein said treatment is continued for at
30 least 2 hours.

9. A method as claimed in any preceding claim wherein the concentration of said carbamate in aqueous solution is in the range of from 0.3M to 6.0M.
10. A method as claimed in claim 9 wherein said concentration is between 1.0M and 3.0M.
11. A method as claimed in any preceding claim wherein said treatment is carried out in the presence of at least one additive.
12. A method as claimed in claim 11 wherein said additive comprises a carbonate or bicarbonate salt.
13. A method as claimed in claim 12 wherein said carbonate or bicarbonate salt comprises caesium carbonate or ammonium bicarbonate.
14. A method as claimed in any preceding claim wherein said treatment is preceded by pre-treatment with acid and washing with water.
15. A method as claimed in claim 14 wherein said pre-treatment and washing is carried out at room temperature.
16. A method as claimed in any one of claims 1 to 13 wherein said treatment is followed by post-treatment with acid and washing with water.
17. A method as claimed in claim 16 wherein said post-treatment and washing is carried out at room temperature.
18. A method as claimed in any one of claims 14 to 17 wherein said acid comprises nitric acid.

19. A method as claimed in any preceding claim whenever applied to the removal of contaminating materials from pipework in the nuclear processing industry.
- 5 20. A method as claimed in claim 19 which comprises the treatment of pipework used in the processing of Highly Active Liquor with an aqueous solution comprising 0.3-1.0M ammonium carbamate and 0.2M caesium carbonate at 60°C for 2 hours.
- 10 21. A method as claimed in claim 19 which comprises the treatment of pipework used in the processing of Highly Active Liquor as follows:
- (a) treatment with 2.0M nitric acid at room temperature; followed by
 - (b) washing with water at room temperature; followed by
 - 15 (c) treatment with 1.0M or 3.0M aqueous ammonium carbamate solution at 60°C for 2 hours.
- 20 22. A method as claimed in claim 19 which comprises the treatment of pipework used in the processing of Highly Active Liquor as follows:
- (a) Treatment with 1.0M or 3.0M aqueous ammonium carbamate solution at 60°C for 2 hours; followed by
 - 25 (b) Treatment with 2.0M nitric acid at room temperature; followed by
 - (c) Washing with water at room temperature.